

Product Data Sheet Neo Armor ™ 4-052-Q11

MEDIUM WEIGHT POLYURETHANE COATED, MACHINE KNITTED LEVEL D GLOVE WITH AN INTEGRAL ELASTICATED WRIST.





Gauge	18 gg
Liner	HPPE
Liner Colours	Salt & Pepper
Dipping Coverage	Palm Coated
Coating	PU
Coating Colour	Black

Features

- Ultra-fine polyurethane coating offers excellent tacky grip in dry and also good in lighter oil conditions for safe and secure handling and extended glove life.
- Low shredding polyurethane coating and continues filament yarn together make much lower tendency to create dust, suitable for clean environment with limited dust.
- Seamless knitted liner with ultra-fine polyurethane coating provides excellent tactile feel, snug fitting and superior dexterity.
- Innovation blend of special high performance fibers, offers excellent mechanical performance
- Product is in compliance with reach directives and azo free dyestuff, content of DMF maintained to the lowest level to make perfect clean glove.
- Soft & Flexible polyurethane coating penetrated inside of knitted fibbers making perfect bonding strength to protect flakiness & coating peeling off.

Applicable Industries

Glove Type

Hazard

- Assembly
- Automotive
- Maintenance
- Paint Line
- Electronics
- Metal Fabrication

Cut Resistant Gloves

Cut



Certifications

CE Category II Certificate EN ISO 21420:2020 EN 388:2016 (4X43D)







DIMENSION

		XS/6	S/7	M/8	L/9	XL/10	XXL/11	XXXL/12
А	Total Glove Length (mm) (±8)	220	210	140	2s0	260	270	280
В	Wrist Length (mm) (±5)	75	75	80	80	85	90	95
С	Wrist width (mm) (±5)	75	80	80	85	90	90	90
D	Palm width (mm) (±5)	90	95	100	105	110	115	120

Packaging

Description

12 Pairs with a Sleeve Pack is packed in a Poly Bag with a User Instruction Sheet (UIS)